

CLG-60 Series

60W Single Output LED Lighting PSU



FEATURES

- Universal AC input / full range
- Short circuit / Overload / Over-voltage / Over-temperature protections
- Built-in active PFC function
- IP67 design for indoor or outdoor installations
- UL1310 Class 2 power unit
- Cooling by free air convection
- 100% full load burn-in test
- High reliability
- Suitable for LED lighting and moving sign applications
- 20V, 27V & 36V versions available

ENVIRONMENTAL

Operating Temp: -30 to +70°C (with de-rating)

Storage Temp: -40 to +80°C

SAFETY / EMC


UL1310 Class 2
CAN/CSA C22.2 No. 223-M91 (except 48V)
EN61347-1
EN61347-2-13
IP67 approved

EN55015
EN55022 (CISPR22) Class B
EN61000-3-2,-3
EN61000-4-2, 3, 4, 5, 6, 8, 11
ENV50204
EN55024
EN61547
Light industry level, criteria A

ELECTRICAL SPECIFICATIONS

Model No.	CLG-60-XX			
XX	12	15	24	48
AC Input	90-264VAC, Single Phase, 47-63Hz			
Power Factor	PF>0.9/230Vac		PF>0.98/115Vac at full load	
DC Output				
Voltage	12V	15V	24V	48V
Current	0-5A	0-4A	0-2.5A	0-1.3A
Rated Power	60W	60W	60W	62.5W
Ripple & noise (p-p) (2)	2V	2.4V	2.7V	4.6V
Voltage Tolerance (3)	±10%			
Line Regulation	±4%			
Load Regulation	±10%			
Overload	95-110%	130% (max)		
Over Voltage	Constant I limiting. Recovers automatically when fault removed.			
Over Temperature	Shut down output voltage. Recovers automatically after temp goes down.			
Dimensions	172(L) x 61.5(W) x 39(H)mm			
Weight	0.86Kg			

Notes: 1. All parameters *NOT* specially mentioned are measured at 230VAC input, rated load and 25°C ambient temperature.
2. Ripple and noise are measured at 20MHz bandwidth by using a 12" twisted pair wire terminated with a 0.1µF and 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line and load regulation.
4. De-rating may be needed under low input voltage conditions. Consult sales for more details.



Specifications subject to change without notice

Ledlite-Power

9, Farnborough Business Centre, Eelmoor Road, Farnborough, Hampshire. GU14 7QN

Tel: +44 (0) 1252 515565 Fax: +44 (0) 1252 546021

e-mail: sales@ledlite-power.com web: www.ledlite-power.com